State of Wisconsin
Department of Natural Resources
Box 450
Madison, Wisconsin 53701

NOTE:
White Copy – Division's Copy
Green Copy – Driller's Copy
Yellow Copy – Owner's Copy

SEP 20 1976

WELL CONSTRUCTOR'S REPORT
Form 3300–15
Rev. 10–75

1. COUNTY: Crawford | CHECK (✓) ONE: ☒ Town ☐ Village ☐ City | Name: Seneca

2. LOCATION: ¼ Section: SE | Section: 10 | Township: 10 N | Range: 6W
OR – Grid or Street No. | Street Name
AND – If available subdivision name, lot & block No.

3. NAME ☒ OWNER ☐ AGENT AT TIME OF DRILLING CHECK (✓) ONE: Jack Haggerty
ADDRESS: R7D
POST OFFICE: Ferryville, Wis. 54628

4. Distance in feet from well to nearest: (Record answer in appropriate block)

Building	Sanitary Bldg. Drain		Sanitary Bldg. Sewer		Floor Drain Connected To		Storm Bldg. Drain		Storm Bldg. Sewer	
	C.I.	Other	C.I.	Other	C.I. Sewer	Other Sewer	C.I.	Other	C.I.	Other
15'	22'									

Street Sewer		Other Sewers		Foundation Drain Connected to:				Sewage Sump		Clearwater Sump	Septic Tank	Holding Tank	Sewage Absorption Unit	85'
San.	Storm	C.I.	Other	Sewer		Sewage Sump		C.I.	Other		60'		Seepage Pit	
				Clearwater Dr.		Clearwater Sump							Seepage Bed	
													Seepage Trench	

Privy	Pet Waste Pit	Pit: Nonconforming Existing		Subsurface Pumproom Nonconforming Existing	Barn Gutter	Animal Barn Pen	Animal Yard	Silo With Pit	Glass Lined Storage Facility	Silo w/o Pit	Earthen Silage Storage Trench Or Pit
		Well									
		Pump									
		Tank									

Temporary Manure Stack	Watertight Liquid Manure Tank	Solid Manure Storage Structure	Subsurface Gasoline or Oil Tank	Waste Pond or Land Disposal Unit (Specify Type)	Other (Give Description)

5. Well is intended to supply water for: Trailer home

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)
10	0 Surface	64	6	64	140

7. CASING, LINER, CURBING AND SCREEN

Dia. (in.)	Material, Weight, Specification & Method of Assembly	From (ft.)	To (ft.)
6	new black steel R.E. 18.97 A-53 Valley Steel Pitless adaptor	0 Surface	64

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
Clay	0 Surface	7
Cement	7	64

9. FORMATIONS

Kind	From (ft.)	To (ft.)
Clay	0 Surface	10
broken limestone	10	25
soft shale stone	25	50
hard shale stone	50	100
sandstone	100	140

10. TYPE OF DRILLING MACHINE USED

☒ Cable Tool	☐ Rotary-hammer w/drilling mud & air	☐ Jetting with
☐ Rotary-air w/drilling mud	☒ Rotary-hammer & air	☐ Air ☐ Water
☐ Rotary-w/drilling mud	☐ Reverse Rotary	

Well construction completed on 8 - 30 - 19 76

11. MISCELLANEOUS DATA

Yield Test: 4 Hrs. at 8 GPM

Depth from surface to normal water level 70 Ft.

Depth of water level when pumping 78 Ft. Stabilized ☒ Yes ☐ No

Well is terminated 12 inches ☒ above ☐ below final grade

Well disinfected upon completion ☒ Yes ☐ No

Well sealed watertight upon completion ☒ Yes ☐ No

Water sample sent to Madison laboratory on 9 - 14 - 19 76

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature: Kenneth Copian — Registered Well Driller

Complete Mail Address: R3 Box 84 Boscobel, Wis. 53805

1020