Depth from surface to normal water level 51 ft. Well sealed watertight upon completion Yes No. Water sample sent to laboratory on: Sept. 28 19 66 Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearb wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, subsurface pumprooms, access pits, etc., should be given on reverse side.	WELL CON	NSTRUCTOR	YS REPORT		wisco	NSIN STAT	E BOARD OF HEALTH		Wei
Section 19 fown 11# Range 5%.	1. COUNTY	<u> </u>		<u> </u>	CHECK	ONE	NAME		
Section 15 Town 11 The Range 57. Section 15 Town 11 The Committed Committee of Section 11 The Committee of Sectio	שפיים	ford Cr	awford		 -				
TOTHER FOLIATION SOURCES (Give deacquires act at demp. quarry. drainage well, shown, poul, biss, etc.) 5. Distance in feet from well to nearesh poulLounc santrage well shown sources (Give deacquires act at demp. quarry. drainage well, shown, poul, biss, etc.) 6. Well is intended to supply water for: 75. Distance 90 75. Distance of the deacquires act at demp. quarry. drainage well, shown, poul, biss, etc.) 6. Well is intended to supply water for: 76. The from (ft) To (ft.) Distance Trees (ft.) To (f	2. LOCATIO	ON (Number a)	nd Street or ? .9 Tow		_		so give subdivision name, lot and block numbers when	available: 10	Time
SOLIDATE BOATA SCHOLDTION SOLIDATE (Browness block) CLEAR WATER DRAIN General surver in appropriate block) CLEAR WATER DRAIN SCHOLDTION SOLIDATE (Browness block) SUPPLY SUPPL	Pau	l Sched	kel			<u> </u>	<u></u>	RECEIVE	
S. Districts in specificial bloods (Record converse in appropriate to appropriate bloods) (Record converse in appropriate to appropriate to appropriate in appropriate to appropriate in appropriate to appropriate in appropriate to appropriate in appropriate in appropriate to appropriate in				RESS				DE A A	NT OF
C. WILLIAM SOURCES (Give description state as dump, quarry, drainage well, attenue, pood, lake, site.) G. Well is intended to supply water for: Parm Parm	5. Distance	e in feet fro	om well to					WASTE OF	AVER DRAIN
OTHER POLLUTION SOURCES (Give description such as deep, quarry, drainage well, stream, poed, lake, etc.) 6. Well is intended to supply water for: Farm	(Record a:				15			DEVELO	Phillips 1
OTHER FOLLUTION SOURCES (Give description such as drapp, quarry, drainage well, stream, pool, bia, cic.) 6. Well is intended to supply water for: Farm 7. DRILHPOLE Dis. (in.) From (ft.) To (ft.) Dis. (in.) From (ft.) To (ft.) 10. Surface 90 Drift Surface 15 8. CASING, LINER, CURBING, AND SCREEN Dis. (in.) Kind and Weight From (ft.) To (ft.) 9. GROUT OR OTHER SEALING MATERIAL Kind Kind From (ft.) To (ft.) 8. CASING, LINER, CURBING, AND SCREEN Dis. (in.) Kind and Weight From (ft.) To (ft.) 9. GROUT OR OTHER SEALING MATERIAL Kind Surface 90 11. MISCELLANEOUS DATA Yield test: 2		•	SEPTIC TAN	K PRIVY	SEEPAGE PIT	ABSORPTI	ON FIELD BARN SILO ABANDONEL VEL	SENK HOLE	139
6. Well is intended to supply water for: Pare To Pare						75			
PRIME PRIME PRIME PRIME PRIME PRIME PRIME PROM	OTHER POI	LUTION SOL	JRCES (Give	description :	such as dump,	quarry, drain	age well, stream, pond, lake, etc.)		
7. DRILLHOLE Dis. (in.) From (ft.) To (ft.) Dis. (in.) From (ft.) To (ft.) 10 Surface 90 Drift Surface 15 6 90 148 If Green Shale 15 90 8. CASING, LINER, CURBING, AND SCREEN From (ft.) To (ft.) Signature 15 6 Pipe 19.45 Surface 90 148 9. GROUT OR OTHER SEALING MATERIAL From (ft.) To (ft.) Signature 15 9. GROUT OR OTHER SEALING MATERIAL From (ft.) To (ft.) 11. MISCELLANEOUS DATA Yield test: B Hrs. at 12 GPM Well is terminated 12 Inches Below Final grade Depth from surface to normal water level S1 ft. Well sealed waterlight upon completion Yes No. No.	6. Well is	intended	to supply	water for	:	····	·		·
Dia. (in.) From (ft.) To (ft.) Dia. (in.) From (ft.) To (ft.) To (ft.) Surface 90 Drift Surface 15 6 90 148 J# Green Shale 15 90 B. CASING, LINER, CURBING, AND SCREEN To (ft.) J# Jordon Sandstone 90 148 6 Pipe 19.45 Surface 90 9. GROUT OR OTHER SEALING MATERIAL Kind Kind and Weight From (ft.) To (ft.) Surface 90 Well construction completed on 9/20 1966 11. MISCELLANEOUS DATA Yield itest: 2			· · ·		·		10 FORMATIONS	. 	
B. CASING, LINER, CURBING, AND SCREEN Sind and Weight From (ft.) To (ft.) Surface 90 148		1	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)		From (ft.)	To (ft.)
8. CASING, LINER, CURBING, AND SCREEN 15. Green Shale 16. Pipe 19.45 90 90 148 90 148 90 90 148 90 90 90 90 90 90 90 90 90 9	10	Surface	90				Three & Alle	Surface	75
B. CASING, LINER, CURBING, AND SCREEN Dia. (in.) Kind and Weight From (ft.) Surface 90 90 148 90 90 90 90 90 90 90 90 90 9									15
Dia (in.) Kind and Weight From (ft.) Surface 90 9. GROUT OR OTHER SEALING MATERIAL Kind From (ft.) Surface 90 9. GROUT OR OTHER SEALING MATERIAL Kind From (ft.) From	R CASING	 		ND SCREE	j .		If Green Shale	15	90
9. GROUT OR OTHER SEALING MATERIAL Kind From (ft.) Surface 90 Well construction completed on 9/20 1966 11. MISCELLANEOUS DATA Yield test: 8 Hrs. at 12 GPM Well is terminated 12 inches below final grade Depth from surface to normal water level 51 ft. Well disinfected upon completion Yes No Well sealed watertight upon completion Yes No Water sample sent to Wadison Iaboratory on: Sept. 28 1966 Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearb wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, surface pumprooms, access pits, etc., should be given on reverse side. BIGNATURE Please do not write in space below COLIFORM TEST RESULT GAS—34 BRS. CONFIRMED REGLARACES		1	-		t	To (ft.)	90 Jordon sandstone	90	148
9. GROUT OR OTHER SEALING MATERIAL Kind From (ft.) To (ft.) Generat Surface 90 Well construction completed on 9/20 19 66 11. MISCELLANEOUS DATA Yield test: 8 Hrs. at 12 GPM Well is terminated 12 inches below final grade Depth from surface to normal water level 51 ft. Well disinfected upon completion Yes Nell disinfected upon completion Yes Nell disinfected upon completion Packet Nell Sealed waterlight upon completion New Neter sample sent to Wadison Iaboratory on: Sept. 28 19 66 Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearth wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sul surface pumprooms, access pits, etc., should be given on reverse side. Death to water level when pumping 55 ft. Well sealed waterlight upon completion Packet Nell Nell Nell Nell Sealed waterlight upon completion Packet Nell Nell Nell Nell Nell Nell Nell Ne	-	Tri	16 4E	•	Surface	90			
Surface Surf		Pipa	13000		· · · · · · · · · · · · · · · · · · ·	70			
Surface 90 Well construction completed on 9/20 1966 11. MISCELLANEOUS DATA Yield test: 8 Hrs. at 12 GPM Well is terminated 12 inches above below final grade Depth from surface to normal water level 51 ft. Well disinfected upon completion Yes No Depth to water level when pumping 53 ft. Well sealed watertight upon completion Yes No Water sample sent to laboratory on: Sept. 28 1966 Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearb wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, subsurface pumprooms, access pits, etc., should be given on reverse side. COMPLETE MAIL ADDRESS Please do not write in space below COLIFORM TEST RESULT REMARKS		<u> </u>							_
Surface Surface 90		Ì							
Surface Surf									
Surface Surf	_			· · ·					
Surface 90 Well construction completed on 9/20 1966 11. MISCELLANEOUS DATA Yield test: 8 Hrs. at 12 GPM Well is terminated 12 inches above below final grade Depth from surface to normal water level 51 ft. Well disinfected upon completion Yes No Depth to water level when pumping 53 ft. Well sealed watertight upon completion Yes No Water sample sent to laboratory on: Sept. 28 1966 Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearb wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, subsurface pumprooms, access pits, etc., should be given on reverse side. COMPLETE MAIL ADDRESS Please do not write in space below COLIFORM TEST RESULT REMARKS	O OPOUT					†			<u> </u>
Well construction completed on 9/20 1966 11. MISCELLANEOUS DATA Yield test: 8 Hrs. at 12 GPM Well is terminated 12 inches below final grade Depth from surface to normal water level 51 ft. Depth from surface to normal water level 51 ft. Well disinfected upon completion Yes No Depth to water level when pumping 53 ft. Well sealed watertight upon completion Yes No Water sample sent to laboratory on: Sept. 28 19 66 Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearb wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, subsurface pumprooms, access pits, etc., should be given on reverse side. SIGNATURE Please do not write in space below COLIFORM TEST RESULT GAS - 24 HRS. GAS - 48 HRS. CONFIRMED REMARKS	9. GROUI			MATERIA	1	To (ft.)			
Well construction completed on \$\frac{9}{20}\$ 19 66 11. MISCELLANEOUS DATA Yield test: \$\frac{8}{20}\$ Hrs. at \$\frac{12}{20}\$ GPM Well is terminated \$\frac{12}{20}\$ inches \$\frac{1}{20}\$ above final grade Depth from surface to normal water level \$\frac{51}{20}\$ ft. Well disinfected upon completion \$\frac{1}{20}\$ Yes \$\frac{1}{20}\$ No. Depth to water level when pumping \$\frac{53}{20}\$ ft. Well sealed watertight upon completion \$\frac{1}{20}\$ Yes \$\frac{1}{20}\$ No. Water sample sent to \$\frac{1}{20}\$ laboratory on: \$\frac{1}{20}\$ Sept. 28 \$\frac{19}{20}\$ 66 Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, surface pumprooms, access pits, etc., should be given on reverse side. SIGNATURE Please do not write in space below COMPLETE MAIL, ADDRESS Please do not write in space below COLIFORM TEST RESULT GAS - 24 HRS. GAS - 48 HRS. CONFIRMED GREMARKS		, .			Surface				
11. MISCELLANEOUS DATA Yield test: R		Cement				90			<u> </u>
Yield test: Second Depth from surface to normal water level S1			5174			<u> </u>	Well construction completed on	9/20	1966
Depth to water level when pumping 53 ft. Well sealed watertight upon completion Feet Section 19 ft. Well sealed watertight upon completion 19 ft. Well sealed watert			_	Hrs.	at 12	GPM	Well is terminated 12 inches		final grade
Depth to water level when pumping 53 ft. Well sealed watertight upon completion Feet No. Water sample sent to laboratory on: Sept. 28 19 66 Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, subsurface pumprooms, access pits, etc., should be given on reverse side. SIGNATURE Please do not write in space below COMPLETE MAIL ADDRESS Please do not write in space below COLIFORM TEST RESULT GAS — 24 HRS. GAS — 48 HRS. CONFIRMED REMARKS	Depth from	m surface to	o normal v	water level	51	ft.	Well disinfected upon completion	∏ Y∈	es 🗌 No
Water sample sent to Madison Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, subsurface pumprooms, access pits, etc., should be given on reverse side. SIGNATURE COMPLETE MAIL ADDRESS Please do not write in space below COLIFORM TEST RESULT GAS—24 HRS. GAS—48 HRS. CONFIRMED REMARKS						ft.	Well sealed watertight upon completion	₹ Ye	es 🔲 No
Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, subsurface pumprooms, access pits, etc., should be given on reverse side. SIGNATURE COMPLETE MAIL ADDRESS Please do not write in space below COLIFORM TEST RESULT GAS—24 HRS. GAS—48 HRS. CONFIRMED REMARKS		_	0			<u>-</u>	lahoratory on:	28 ant	19 66
wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, subsurface pumprooms, access pits, etc., should be given on reverse side. SIGNATURE COMPLETE MAIL ADDRESS Please do not write in space below COLIFORM TEST RESULT GAS — 24 HRS. GAS — 48 HRS. CONFIRMED REMARKS	Vaus onin	ion concer			hararde i	nformation			
Please do not write in space below COLIFORM TEST RESULT GAS - 24 HRS. GAS - 48 HRS. CONFIRMED GREMARKS	wells, scre	eens, seals,	type of	casing joi	nts, method	d of finish	ing the well, amount of cement used in		
Please do not write in space below COLIFORM TEST RESULT GAS — 24 HRS. GAS — 48 HRS. CONFIRMED REMARKS	SIGNATURE		0		· · · · · · · · · · · · · · · · · · ·			····-	
Please do not write in space below COLIFORM TEST RESULT GAS — 24 HRS. GAS — 48 HRS. CONFIRMED REMARKS	D.		1.00	7	المستفاسية	/all D⊒ll			
COLIFORM TEST RESULT GAS — 24 HRS. GAS — 48 HRS. CONFIRMED TREMARKS	<u>viii</u>	me (noo	K	egistered W Please	do not w	rite in space below	20100	
04≈	_	řešt result	г					ARKS	
	1042			ľ		ĺ			