WELL CONSTRUCTOR'S REPORT FORM 3300-15	JUN 4 1973	NOTE DEPARTMENT OF N	WISCONSIN ATURAL RESOURCES
CRAWFORN	GREEN CO	PY — IMVISION S COPY	450 sconsin 53701
1. COUNTY Strant	CHECK ONE	Village City NAME	utan)
2. LOCATION - ¼ Section Section	Township Range	3. OWNER AT TIME OF DRILLING	1
OR - Grid or street no: Street name	11 14 1 0 VY	ADDRESS R 7 D	Lon
AND - If available subdivision name, lot of block is	no.	POST OFFICE S. P. L.	N 5465
4. Distance in feet from well to nearest:	BUILDING SANITARY SEWER	FLOOR DRAIN FOUNDATION DRAIN C. I. TILE SEWER CONNECTED INDEPENDENT	WASTE WATER DRAIN
(Record answer in appropriate block)	30 80'		80
CLEAR WATER DRAIN SEPTIC TANK PRIVY C. I. TILE 90'	SEEPAGE PIT ABSORPTION 75	FIELD BARN SILO ABANDONED WELL S	INK HOLE
OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)			
5. Well is intended to supply water for: Country home!			
6. DRILLHOLE Dia. (in.) From (ft.) To (ft.) Dia. (in		9. FORMATIONS Kind	From (ft.) To (ft.)
10 Surface 52 6	52120	CD	Surface /5
		1 de 1 de	1 = 4n
7. CASING, LINER, CURBING, AND SCR	1	hard shalaston	40 90
Dia. (in.) Kind and Weight Rew Black stee	Surface 52	Sandstone	
- Plainend 19.1	8 00000	gandstone	90 120
		<u> </u>	
· · · · · · · · · · · · · · · · · · ·			
		·	
8. GROUT OR OTHER SEALING MATER	IAL	10. TYPE OF DRILLING MACHINE USED	:
Kind	From (ft.) To (ft.)	Cable Tool Direct Rotary	Reverse Rotary
Clay	Surface /5	Rotary — air w/drilling mud with drilling mud & air	Jetting with Air Water
11. MISCELLANEOUS DATA	15 52	Well construction completed on 5-2.	3- 19 73 above
Yield test: 4 Hrs. a	et 8 GPM	Well is terminated // inches	below final grade
Depth from surface to normal water level	60 ft.	Well disinfected upon completion	Yes 🔲 No
Depth to water level when pumping	64 ft.	Well sealed watertight upon completion	Yes 🔲 No
Water sample sent to Madi	son	laboratory on: 5 –	29- 1973
Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.			
SIGNATURE .		COMPLETE MAIL ADDRESS BORE OF	Q_
Okenneth Copian Registered Well Driller R3Box84 Miss, 53805 Please do not write in space below			
COLIFORM TEST RESULT OH H REV. 3-71	· · · · · · · · · · · · · · · · · · ·	- 48 HRS. CONFIRMED REMARK	KS