

1. COUNTY Crawford CHECK (✓) ONE: Town Village City Name Clayton

2. LOCATION SE, SE 1/4 Section NE Section 31 Township 11N Range 3W 3. NAME OWNER AGENT AT TIME OF DRILLING CHECK (✓) ONE
 ADDRESS Village of Soldiers Grove
P.O. Box 121

AND - If available subdivision name, lot & block No. POST OFFICE Soldiers Grove, WI 54655

4. Distance in feet from well to nearest: (Record answer in appropriate block)

| Building | | Sanitary Bldg. Drain | | Sanitary Bldg. Sewer | | Floor Drain Connected To: | | Storm Bldg. Drain | | Storm Bldg. Sewer | |
|----------|-------|----------------------|-------|----------------------|-------|---------------------------|-------------|-------------------|-------|-------------------|-------|
| C.I. | Other | C.I. | Other | C.I. | Other | C.I. Sewer | Other Sewer | C.I. | Other | C.I. | Other |

Street Sewer: San. Storm Other Sewers: C.I. Other Foundation Drain Connected to: Sewer Sewage Sump Clearwater Dr. Sewage Sump Clearwater Sump Sewage Sump C.I. Other Clearwater Sump Septic Tank Holding Tank Sewage Absorption Unit: Seepage Pit Seepage Bed Seepage Trench

Privy: Pet Waste Pit Pit: Nonconforming Existing Well Pump Tank Subsurface Pumproom Nonconforming Existing Barn Gutter Animal Barn Pen Animal Yard Silo With Pit Glass Lined Storage Facility Silo w/o Pit Earthen Silage Storage Trench Or Pit

Temporary Manure Stack Watertight Liquid Manure Tank Solid Manure Storage Structure Subsurface Gasoline or Oil Tank Waste Pond or Land Disposal Unit (Specify Type) Other (Give Description)

5. Well is intended to supply water for: Village of Soldiers Grove

6. DRILLHOLE

| Dia. (in.) | From (ft.) | To (ft.) | Dia. (in.) | From (ft.) | To (ft.) |
|------------|------------|------------|------------|------------|------------|
| <u>24</u> | Surface | <u>150</u> | <u>15</u> | <u>150</u> | <u>170</u> |

9. FORMATIONS

| Kind | From (ft.) | To (ft.) |
|---------------------------------|------------|------------|
| <u>Sandstone + Shale Mixed</u> | Surface | <u>145</u> |
| <u>Sandstone, Streaks Shale</u> | <u>145</u> | <u>160</u> |
| <u>Sandstone</u> | <u>160</u> | <u>490</u> |

7. CASING, LINER, CURBING AND SCREEN

| Dia. (in.) | Material, Weight, Specification & Method of Assembly | From (ft.) | To (ft.) |
|------------|--|------------|------------|
| <u>16"</u> | <u>new pipe ASTM A53 375 wall</u> | Surface | <u>150</u> |
| <u>10"</u> | <u>new pipe 365 wall ASTM A53</u> | <u>0</u> | <u>170</u> |

8. GROUT OR OTHER SEALING MATERIAL

| Kind | From (ft.) | To (ft.) |
|-----------------------|------------|------------|
| <u>Cement + Water</u> | Surface | <u>170</u> |

650 bags

10. TYPE OF DRILLING MACHINE USED

Cable Tool Rotary-hammer w/drilling mud & air Jetting with Air Water

Rotary-air w/drilling mud Rotary-hammer & air

Rotary-w/drilling mud Reverse Rotary

Well construction completed on 1-30 1979

11. MISCELLANEOUS DATA

Yield Test: 4 Hrs. at 650 GPM

Depth from surface to normal water level 72 Ft.

Depth of water level when pumping 120 Ft. Stabilized Yes No

Well is terminated 38 inches above final grade below

Well disinfected upon completion Yes No

Well sealed watertight upon completion Yes No

Water sample sent to S.L.H. laboratory on 2/7 1979

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature Maurice Hoffman
 Registered Well Driller

Complete Mail Address R. 4, Box 69, Wisconsin Dells, WI
53965

1059 DIST FILE SGS