

MAR 29 1978

NOTE: APR 12 1978
White Copy - Division's Copy
Green Copy - Driller's Copy
Yellow Copy - Owner's Copy

1. COUNTY Crawford CHECK (✓) ONE: Town Village City Name Clayton

2. LOCATION NW Section 31 Township 11N Range 4W 3. NAME OWNER AGENT AT TIME OF DRILLING CHECK (✓) ONE
OR - Grid or Street No. Street Name ADDRESS Robert Olson
RFD

AND - If available subdivision name, lot & block No. POST OFFICE Soldiers Grove, Wis, 54655

4. Distance in feet from well to nearest: (Record answer in appropriate block) Building 15'

Sanitary Bldg. Drain		Sanitary Bldg. Sewer		Floor Drain Connected To:		Storm Bldg. Drain		Storm Bldg. Sewer	
C.I.	Other	C.I.	Other	C.I. Sewer	Other Sewer	C.I.	Other	C.I.	Other

Street Sewer: San. Storm Other Sewers: C.I. Other Foundation Drain Connected to: Sewage Sump: C.I. Other Clearwater Sump: Clearwater Dr. Sewage Sump Clearwater Sump Septic Tank: 50 Holding Tank: Sewage Absorption Unit: 65' Seepage Pit Seepage Bed Seepage Trench

Privy: Pit: Nonconforming Existing Well Pump Tank Subsurface Pumproom: Nonconforming Existing Barn Gutter Animal Barn Pen Animal Yard Silo With Pit Glass Lined Storage Facility Silo w/o Pit Earthen Silage Storage Trench Or Pit

Temporary Manure Stack: Watertight Liquid Manure Tank Solid Manure Storage Structure Subsurface Gasoline or Oil Tank Waste Pond or Land Disposal Unit (Specify Type) Other (Give Description)

5. Well is intended to supply water for: Country home

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)
<u>10</u>	<u>Surface</u>	<u>85</u>	<u>6</u>	<u>85</u>	<u>120</u>

9. FORMATIONS

Kind	From (ft.)	To (ft.)
<u>Clay & soft sand</u>	<u>Surface</u>	<u>37</u>
<u>soft shalestone</u>	<u>37</u>	<u>60</u>
<u>hard shalestone</u>	<u>60</u>	<u>100</u>
<u>hard sandstone</u>	<u>100</u>	<u>120</u>

7. CASING, LINER, CURBING AND SCREEN

Dia. (in.)	Material, Weight, Specification & Method of Assembly	From (ft.)	To (ft.)
<u>6</u>	<u>new black steel R.E. 18.97</u> <u>A-53</u> <u>Valley Steel</u> <u>Pitless adaptor</u>	<u>Surface</u>	<u>85</u>

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
<u>loose sand</u>	<u>Surface</u>	<u>7</u>
<u>Cement</u>	<u>7</u>	<u>85</u>

10. TYPE OF DRILLING MACHINE USED

Cable Tool Rotary-hammer w/drilling mud & air Jetting with Air Water

Rotary-air w/drilling mud Rotary-hammer & air

Rotary-w/drilling mud Reverse Rotary

Well construction completed on 3-7- 1978

11. MISCELLANEOUS DATA

Yield Test: 3 Hrs. at 5 GPM

Depth from surface to normal water level 55 Ft.

Depth of water level when pumping 62 Ft. Stabilized Yes No

Well is terminated 10 inches above below final grade

Well disinfected upon completion Yes No

Well sealed watertight upon completion Yes No

Water sample sent to Madison laboratory on 3-22- 1978

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature Kenneth Coplan Registered Well Driller Complete Mail Address Boscobel, Wis.
R3 Box 84 53805