

OCT 5 1973

WELL CONSTRUCTOR'S REPORT
FORM 3300-15

STATE OF WISCONSIN
DEPARTMENT OF NATURAL RESOURCES
Box 450
Madison, Wisconsin 53701

NOTE

WHITE COPY - DIVISION'S COPY
GREEN COPY - DRILLER'S COPY
YELLOW COPY - OWNER'S COPY

1. COUNTY Crawford CHECK ONE Town Village City NAME Freeman

2. LOCATION - 1/4 Section SE Section 23 Township 10N Range 7W 3. OWNER AT TIME OF DRILLING Morris Rutter

OR - Grid or street no. Sec 33 ? Street name T11N R6W?? ADDRESS R7D

AND - If available subdivision name, lot & block no. POST OFFICE De Soto, Wis., 54624

4. Distance in feet from well to nearest: BUILDING SANITARY SEWER FLOOR DRAIN FOUNDATION DRAIN WASTE WATER DRAIN
(Record answer in appropriate block) 10' 23' C.I. TILE C.I. TILE SEWER CONNECTED INDEPENDENT C.I. TILE 23'

CLEAR WATER DRAIN SEPTIC TANK PRIVY SEEPAGE PIT ABSORPTION FIELD BARN SILO ABANDONED WELL SINK HOLE
C.I. TILE 50' 70'

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Country home

6. DRILLHOLE						9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
10	Surface	40	6	40	100	Clay	Surface	15
						hard sandstone	15	100

7. CASING, LINER, CURBING, AND SCREEN			
Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
6	new black steel plain end 19.18	Surface	40

8. GROUT OR OTHER SEALING MATERIAL Kind From (ft.) To (ft.) Clay Surface 15 Cement 15 40

10. TYPE OF DRILLING MACHINE USED
 Cable Tool Direct Rotary Reverse Rotary
 Rotary - air w/drilling mud Rotary - hammer with drilling mud & air Jetting with Air Water

11. MISCELLANEOUS DATA
 Yield test: 2 Hrs. at 5 GPM
 Well construction completed on 9-10-1973
 Well is terminated 48 inches below final grade

Depth from surface to normal water level 23 ft. Well disinfected upon completion Yes No
 Depth to water level when pumping 28 ft. Well sealed watertight upon completion Yes No

Water sample sent to Madison laboratory on: 10-1973

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Kenneth Coplan Registered Well Driller COMPLETE MAIL ADDRESS R3 Box 84 Boscobel Wis., 53805

COLIFORM TEST RESULT 118 GAS - 24 HRS. GAS - 48 HRS. CONFIRMED REMARKS
REV. 3-71