

NOV 10 1981 WCO

1. COUNTY Crawford CHECK (✓) ONE: CLAYTON? Name Soldiers Grove  
 Town  Village  City  
 2. LOCATION NW Section 10 Township 10N Range 3W 3. NAME  OWNER  AGENT AT TIME OF DRILLING CHECK (✓) ONE  
Ed Merg  
 OR - Grid or Street No. Street or Road Name ADDRESS Rt. 2 Box 48  
 AND - If available subdivision name, lot & block No. POST OFFICE Soldiers Grove ZIP CODE WF

4. Distance in feet from well to nearest: (Record answer in appropriate block) 30'  
 Building Sanitary Bldg. Drain Sanitary Bldg. Sewer Floor Drain Connected To: Storm Bldg. Drain Storm Bldg. Sewer  
 C.I. Other C.I. Other C.I. Sewer Other Sewer C.I. Other C.I. Other  
 Street Sewer Other Sewers Foundation Drain Connected to: Sewage Sump Clearwater Sump Clearwater Sump Septic Tank Holding Tank Sewage Absorption Unit Manure Hopper or Retention or Pneumatic Tank  
 San. Storm C.I. Other Sewer Sewage Sump Clearwater Dr. C.I. Other Clearwater Sump 80' Seepage Pit Seepage Bed Seepage Trench  
 Privy Pet Waste Pit Pit: Nonconforming Existing Subsurface Pumproom Barn Gutter Animal Barn Pen Animal Yard Silo With Pit Glass Lined Storage Facility Silo w/o Pit Earthen Silage Storage Trench Or Pit Earthen Manure Basin  
 Temporary Manure Stack or Platform Watertight Liquid Manure Tank or Basin Manure Pressure Pipe Subsurface Gasoline or Oil Tank Waste Pond or Land Disposal Unit (Specify Type) Manure Storage Basin Concrete Floor Only Concrete Floor and Partial Concrete Walls Other (Describe)

5. Well is intended to supply water for: Country home 9. FORMATIONS

Kind	From (ft.)	To (ft.)
<u>topsoil</u>	<u>Surface</u>	<u>11</u>
<u>sandstone</u>	<u>11</u>	<u>69</u>
<u>limestone hard</u>	<u>69</u>	<u>127</u>
<u>hard sandstone</u>	<u>127</u>	<u>211</u>
<u>hard shalestone</u>	<u>211</u>	<u>240</u>

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)
<u>10</u>	<u>Surface</u>	<u>128</u>	<u>6</u>	<u>128</u>	<u>240</u>

7. CASING, LINER, CURBING AND SCREEN

Dia. (in.)	Material, Weight, Specification	From (ft.)	To (ft.)
<u>6</u>	<u>P.E. 18.97 1/2"</u>	<u>Surface</u>	<u>128</u>
	<u>A-53 Kent Steel</u>		
	<u>Pitless adapter</u>		

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
<u>clay</u>	<u>Surface</u>	<u>8</u>
<u>cement</u>	<u>8</u>	<u>128</u>

10. TYPE OF DRILLING MACHINE USED

Cable Tool  Rotary-hammer w/drilling mud & air  Jetting with

Rotary-air w/drilling mud  Rotary-hammer & air  Air

Rotary-w/drilling mud  Reverse Rotary  Water

Well construction completed on 7-3 1981

11. MISCELLANEOUS DATA

Yield Test: 2 Hrs. at 8 GPM Well is terminated 15 inches  above final grade  below

Depth from surface to normal water level 180 Ft. Well disinfected upon completion  Yes  No

Depth of water level when pumping 190 Ft. Stabilized  Yes  No Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on 11-3 1981

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature Keneth Corpean Registered Well Driller Business Name and Complete Mailing Address Keneth Corpean & Sons, Inc  
Rt. 2 Box 4 Boscobel, WI 53805

136