

SPOT CHECK

NOTE:
 White Copy - Division's Copy
 Green Copy - Driller's Copy
 Yellow Copy - Owner's Copy

APR 13 1984

1. COUNTY **CRAWFORD** CHECK (✓) ONE: Town Village City Name **CLAYTON**

2. LOCATION **NW** 1/4 Section or Gov't. Lot Section **22** Township **10N** Range **3W** 3. NAME OWNER AGENT AT TIME OF DRILLING CHECK (✓) ONE **SAINT PHILIPS CHURCH**

OR - Grid or Street No. Street or Road Name ADDRESS **ROLLING GROUND, WI.**

AND - If available subdivision name, lot & block No. POST OFFICE ZIP CODE

4. Distance in feet from well to nearest: (Record answer in appropriate block) Building **15'** Sanitary Bldg. Drain C.I. Other Sanitary Bldg. Sewer C.I. Other Floor Drain Connected To: C.I. Sewer Other Sewer Storm Bldg. Drain C.I. Other Storm Bldg. Sewer C.I. Other

Street Sewer San. Storm Other Sewers C.I. Other Foundation Drain Connected to: Sewer Sewage Sump Clearwater Dr. Sewage Sump Clearwater Sump Sewage Sump C.I. Other Clearwater Sump Septic Tank Holding Tank Sewage Absorption Unit Seepage Pit Seepage Bed Seepage Trench Manure Hopper or Retention or Pneumatic Tank

Privy Pet Waste Pit Pit: Nonconforming Existing Well Pump Tank Subsurface Pumproom Nonconforming Existing Barn Gutter Animal Barn Pen Animal Yard Silo With Pit Glass Lined Storage Facility Silo w/o Pit Earthen Silage Storage Trench Or Pit Earthen Manure Basin

Temporary Manure Stack or Platform Watertight Liquid Manure Tank or Basin Manure Pressure Pipe Subsurface Gasoline or Oil Tank Waste Pond or Land Disposal Unit (Specify Type) Manure Storage Basin Concrete Floor Only Concrete Floor and Partial Concrete Walls Other (Describe) **SPOTCHECK FOR D.T. SCHOOL & CEMETERY**

5. Well is intended to supply water for: **COUNTRY HOME AND CHURCH**

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)
10"	Surface	274			
6"	274	340			

7. CASING, LINER, CURBING AND SCREEN

Dia. (in.)	Material, Weight, Specification Mfg. & Method of Assembly	From (ft.)	To (ft.)
6	NEW BLACK STEEL PLAIN END	Surface	274
	A-53 18.97		

9. FORMATIONS

Kind	From (ft.)	To (ft.)
CLAY-LOOSE ROCK	Surface	15
LIMESTONE	15	110
SOFT SANDSTONE	110	200
SOFT SHALESTONE	200	260
HARD SHALESTONE	260	340

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
CEMENT	Surface	274

10. TYPE OF DRILLING MACHINE USED

Cable Tool Rotary-hammer w/drifting mud & air Jetting with Air Water

Rotary-air w/drilling mud Rotary-hammer & air

Rotary-w/drilling mud Reverse Rotary

Well construction completed on **3-28 1984**

11. MISCELLANEOUS DATA

Yield Test: **3** Hrs. at **15** GPM Well is terminated **10** inches above final grade below

Depth from surface to normal water level **260** Ft. Well disinfected upon completion Yes No

Depth of water level when pumping **275** Ft. Stabilized Yes No Well sealed watertight upon completion Yes No

Water sample sent to **MADISON** laboratory on **4-11 1984**

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side.

Signature **143** **Harrold Coyner** Registered Well Driller

Business Name and Complete Mailing Address **CORPIAN WELL DRILLING**
RT. 2 BOX 4, BOSCOBEL, WI. 53605