State of Wisconsin Department of Natural Resources Box 7921

NOTE:

WELL CONSTRUCTOR'S REPORT Form 3300-15 MAR 2 5 1961 Rev. 12-76 White Copy Division's Copy Green Copy - Driller's Copy Madison, Wisconsin 53707 Yellow Copy - Owner's Copy MCD Wauzeka Colombia 1. COUNTY CHECK (✓) ONE: Name Crawford NUNWSE, ☐ Village __ City 3. NAME XX OWNER AGENT AT TIME OF DRILLING CHECK (4) ONE Range_ Township. % Section Section 4W 18 7N Roger Geisler 2. LOCATION ADDRESS OR - Grid or Street No. Street Name Wauzeka, Wis 53826 Der man from MSA AND - If available subdivision name, lot & block No. POST OFFICE Floor Drain Connected To: 4. Distance in feet from well Building Sanitary Bldg, Drain Sanitary Bldg, Sewer Storm Bldg, Sewer Storm Bldg, Drain to nearest: {Record Other C.I. C.I. Other C.I. Sewer |Other Sewer| C.I. Other C.I. Other answer in appropriate 15 block) Street Sewer Foundation Drain Connected to Other Sewers Clearwater Holding Sewage Absorption Unit Sewage Sump Septic Tank Sump Tank Sewage **Շ**.เ.` Other Seepage Pit C.I. Other San. Storm Sewer Sump 30 504 Seepage Bed Clearwater Clearwater Sump Seepage Trench Pit: Nonconforming Existing Privy Pet Animal |Silo Glass Lined | Silo Subsurface Pumproom Barn Animal Earthen Silage Waste With Pit Storage w/o Pit Gutter Barn Yard Storage Trench Or Nonconforming Existing Well Pit Pen Facility Pump Tank Solid Manure Storage Other (Give Description) Temporary Watertight Waste Pond or Land Subsurface Liquid Manure Disposal Unit Manure Gasoline or Stack Tank Structure Off Tank (Specify Type) 5. Well is intended to supply water for: 9. FORMATIONS Dwelling From (ft.) To (ft.) Kind 6. DRILLHOLE Topsoil From (ft.) Dia. (in.) From (tt.) To (ft.) Dia. (in.) To (ft.) Surface Sand 10 40 40 10 80 Surface Andstone 10 80 7. CASING, LINER, CURBING AND SCREEN Material, Weight, Specification To (ft.) Dia. (in.) & Method of Assembly |- From (ft.)| soute to Mis Helpick 18:97P.E. Sced 40 6 40 Surface Pitless Astm-A-53 American Steel 10. TYPE OF DRILLING MACHINE USED Rotary-hammer w/drilling XX Cable Tool Jetting with mud & air 8. GROUT OR OTHER SEALING MATERIAL To (ft.) Rotary-air Rotary-hammer Air From (ft.) w/driffing mud & air Water Backfill W/ Native Soil Rotary-w/drilling ş Surface Reverse Rotary Cement grout 40 Feb 23, క 1981 Well construction completed on MISCELLANEOUS DATA XXabove final grade Well is terminated _ inches below **GPM** Yield Test: __ Hrs. at XX Yes 🗀 No 21 Ft. Well disinfected upon completion Depth from surface to normal water level Depth of water level Yes No Well sealed watertight upon completion XX Yes 🗀 No when pumping Ft. State Feb 23 19 81 laboratory on Water sample sent to Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, method of finishing the well, amount of cement used in grouting, blasting, etc., should be given on reverse side. Complete Mail Address Signature Albin Herbeck Box 136 Richland Center, Wis 53581

Registered Well Driller

110