WELL CONSTRUCTOR'S REPORT FORM 3300-15

COLIFORM TEST RESULT

264

REV. 3-71

GAS - 24 HRS.

NOTE

STATE OF WISCONSIN DEPARTMENT OF NATURAL RESOURCES Box 450

WHITE COPY - DIVISION'S COPY Madison, Wisconsin 53701 GREEN COPY - DRILLER'S COPY YELLOW COPY - OWNER'S COPY 1. COUNTY CHECK ONE NAME Crawford Town Village 🗓 City Praire Du Chien 2. LOCATION -**%** Section Section Township 3. OWNER AT TIME OF DRILLING Range 7 - N6-W Charles Lange OR - Grid or street no. Street name **ADDRESS** Farm Lot 20 Cliffwood Dr. 216 N. Michigan St. AND -If available subdivision name, lot & block no. POST OFFICE Ahrens Coulee Lot 9 Blk. 2 Praire Du Chien// Wisc. BUILDING SANITARY SEWER FLOOR DRAIN 4. Distance in feet from well to nearest: FOUNDATION DRAIN WASTE WATER DRAIN SEWER CONNECTED INDEPENDENT C. I. TILE C. I. TILE C. I. THE (Record answer in appropriate block) 48 Not Yet Installed CLEAR WATER DRAIN | SEPTIC TANK | PRIVY | SEEPAGE PIT | ABSORPTION FIELD ABANDONED WELL BARN SILO SINK HOLE C. I. TILE Ndne None OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.) None 5. Well is intended to supply water for: House 6. DRILLHOLE 9. FORMATIONS Dia. (in.) From (ft.) To (ft.) Dia. (in.) From (ft.) To (ft.) From (ft.) Kind To (ft.) Surface Surface 35 10 6 120 Black Dirt <u>Yellow Clay</u> 35 7. CASING, LINER, CURBING, AND SCREEN Dia. (in.) Kind and Weight To (ft.) Gray Mud From (ft.) 70 Surface New Steel P. E. 103 Orange Sand & Drift <u>18.97# per Ft.</u> Brn. Sandy Drift 95 <u>Orange Sand & Drift</u> 95 100 Jordan Sandstone 100 120 8. GROUT OR OTHER SEALING MATERIAL 10. TYPE OF DRILLING MACHINE USED To (ft.) Kind From (ft.) XX able Tool Reverse Rotary Direct Rotary Surface ___ Rotary – air Rotary - hammer Jetting with Puddled Clay 35 w/drilling mud with drilling mud & sir ☐ Air ☐ Water 7 - 2119 72 Well construction completed on <u>Drive Shoe</u> 35 103 11. MISCELLANEOUS DATA above x final grade 11 Well is terminated inches **GPM** below Yield test: Hrs, at \mathbf{x} Well disinfected upon completion ft. Depth from surface to normal water level \mathbf{x} Well sealed watertight upon completion No ft. 40 Depth to water level when pumping State Lab. of Hygiene; Madison, Wisc. 7-25 **19**72 laboratory on: Water sample sent to Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side. Amane Lubburg. 410 COMPLETE MAIL ADDRESS SIGNATURE Duane Lubbers Duane Lubbers Farmersburg. Iowa 52047 Registered Well Driller Please do not write in space below

GAS - 48 HRS.

CONFIRMED

REMARKS