W	ELL C	ONSTRUCTO			on Reverse Side		E G B
1. County - Prayford.					Town Wauseka	ENVIRONAL 18	
2. Location Sec 28, 77N,5W)	City Gr. Hywey S.	ictur	TION
Owne	r or Ag	entH	al R	ussel_	0 1	7	
Addre	- €	Bridge	report	- Wx			· *
		nearest: Buil	ding S	ftran	verft; drainft; s	antia tanl	·
		ter bed			•	ерис цапк	<u></u>
Well	is intend	led to supply v	vater for:	Hon	¥		
	LHOLE			·	10. FORMATIONS:		
Dia. (in.)		From (ft.)		o (ft.)	Kind	Thick-	Total Depth
6	· ·			5/	Top Soil	(ft.)	(fū.)
				ه د	Line Rock.	19	92
					Skile	32.	56
CASI	 [NG AN]	D LINER PIP	—⊦—— E OR CUI	RBING:			
Dia. (in.)		Kind	From (ft.)	To (ft.)			
6.	Standard Cements in		O .	21			<u> </u>
-	Cen	until in	·	<u> </u>			
	· · · · · · · · · · · · · · · · · · ·						
_		<u> </u>		.[<u> </u>
. GROUT:			; Frem	To (ft.)			
			. 1			· - · · · · · · · · · · · · · · · · · · ·	
				<u></u>			
	· · · · ·						<u> </u>
eld test pth fro ater-lev ater sa	om surfavel when mple ser	EOUS DATA Hrs. at the to water: pumping: to laborator on Au	25 25 y at	ft.	Was the well sealed watertig	ent grade. on complet the upon c	inche ion? completion
mature	Re	gistered Well Dr	iller		Complete Mail	Address	? <u>`</u>

cr 372