are a mal

NOTE

STATE OF WISCONSIN
DEPARTMENT OF NATURAL RESOURCES
Box 450
Madison, Wisconsin 53701

WHITE COPY - DIVISION'S COPY GREEN COPY - DRILLER'S COPY YELLOW COPY - OWNER'S COPY

1. COUNTY Crawbord	Cl Tow	IECK ONE	Village	NAME	dunal	
	OCATION - 1/4 Section Section Township Range		3. OWNER AT TIME OF DRILLING			
OR – Grid or street no. Street na		6 W	ADDRESS	see at	ren	<u></u>
AND -I f available subdivision name, lot & block no.			P7D			
	POST OFFICE Prairie du Chien Wi 5382					
4. Distance in feet from well to nearest:		NITARY SEWER		UNDATION DRAIN NNECTED INDEPENDEN		TER DRAIN TILE
(Record answer in appropriate block)	10 2	(5)			<u> </u>	
CLEAR WATER DRAIN SEPTIC TANK PR	UVY SEEPAGE PIT		5 200 200	1	SINK HOLE	
OTHER POLLUTION SOURCES (Give descrip	ption such as dump, q	<u> </u>		1	"	· · · · · · · · · · · · · · · · · · ·
5. Well is intended to supply water for:	-				·	
	Couri	tru	home			
6. DRILLHOLE	1		9. FORMATIONS	_	1	
, 0 ,54	a. (in.) From (ft.)	To (ft.)	Kind		From (ft.)	To (ft.)
& Surface			loose s	and	Surface	50
		1	loose s gravel	Rediginto	, 50	60
7. CASING, LINER, CURBING, AND S	CREEN		1	-feari	racj.	
Dia. (in.) Kind and Weight	Fr/om (ft.)	1	* .		7	
6 plainend 18	97 Surface	56	.			
A-53	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	·				
Valley St.	-0	<i>:</i>				
		 	:			
8. GROUT OR OTHER SEALING MAT	TERIAL	1	10. TYPE OF DRILLI	NG MACHINE USED		·····
Kind From (ft.) To (ft.)			Cable Tool Direct Rotary Reverse Rotary			
loose sand Surface		50	Rotary – air w/drilling mud Rotary – hammer with drilling mud & air Air Wate		_	
			Well construction comp	eleted on 12 - 3		19 75
11. MISCELLANEOUS DATA Hrs. at 8 GPM			Well is terminated / 2 inches above below final grade			
Depth from surface to normal water leve	, \ 3	O ft.	Well disinfected upon o	ompletion	∑ Ye	s 🗀 No
Depth to water level when pumping 30 ft.			Well sealed watertight upon completion X Yes No			
	dison		<u> </u>	poratory on: /	15 -	1976
Your opinion concerning other pollution	<u> </u>		· · · · · · · · · · · · · · · · · · ·		'	
type of casing joints, method of finishing be given on reverse side.		of cement use	d in grouting, blasting, su	b-surface pumprooms,	access pits, et	
SIGNATURE			COMPLETE MAIL ADDR	ESS D. (? .	
Zemeth Corpian	Registered We	II Driller	COMPLETE MAIL ADDR	mi,	<u>5380</u>	5
	GAS – 24 HRS		te in space below – 48 HRS. CONFIR	MED REMAR	RKS	
COLIFORM TEST RESULT 450 REV. 3–71	UAS - 24 IIKS	·	TO III.O. CONTIN	KLMAI		