

WELL LOG and REPORT

For method of making report, refer to bulletin entitled "Well Construction Report," 7-5-1939.

In this column indicate the kind of casing, liner, shoe and other accessories used.

WELL DIAGRAM
Use a red line to show casing or liner pipe. Use black for drill or borehole.

In this column state the kind of formations penetrated, their thickness in feet and if water bearing.

Record of FINAL Pumping test

5 in Standard Casing
liner shoe.
Cement Plat form.

Inches Diameter		Depth
2 3 4 5 6 8 10 12 14 16 18		
-----		25
-----		50
-----		70 ft
-----		75
-----		80 ft
-----		100
-----		150
-----		200
-----		400
-----		800
-----		1200

20 ft surface clay.

gravel and sand
40 ft.

20 ft of shale.

Depth of well.

Duration of test
Hours 4 hrs.

Pumping rate
G.P.M. 10 gal.

Depth of pump in well. Ft. 30 ft.

Standing water-level (from surface)
Ft. 20 ft.

Water-level when pumping Ft. 20 ft

Water. End of test.
Clear Cloudy _____ Turbid _____

Was the well sterilized?
Yes No _____

To which laboratory was sample sent?
state

Date Aug 5

Was the well sealed on completion?
Yes No _____

How high did you leave the casing-pipe above grade?
1 ft.

Well was completed
Date June 15 42

Well Driller
E. S. Water
Signature

Draw the diagram to show the right half only.