

# WELL LOG and REPORT

For method of making report, refer to bulletin entitled "Well Construction Report," 7-5-39. Accuracy is essential.

In this column indicate the kind of casing, liner, shoe and other accessories used.

**WELL DIAGRAM**  
Use a red line to show casing or liner pipe. Use black for drill or borehole.

In this column state the kind of formations penetrated, their thickness in feet and if water bearing.

Record of FINAL Pumping test

128 feet of 5" Standard Steel Black Casing.

Inches Diameter		Depth
2 3 4 5 6 8 10 12 14 16		
		25
		50
		75
		100
		150
		200
		400
		800
		1200

139' depth.

Sand and Muddy WATER

White SAND ROCK.

Duration of test Hours 8 hrs

Pumping rate G.P.M. 8 gal P.M.

Depth of pump in well. Ft. 64 feet

Standing water-level (from surface) Ft. 45 feet

Water-level when pumping Ft. Same

Water. End of test.  
Clear Clear  
Cloudy \_\_\_\_\_  
Turbid \_\_\_\_\_

Was the well sterilized?  
Yes Yes No \_\_\_\_\_

To which laboratory was sample sent?  
Madison  
Date Nov 18, 1941

Was the well sealed on completion?  
Yes Yes No \_\_\_\_\_

How high did you leave the casing-pipe above grade?  
12 inches

Well was completed Date Nov 15, 1941

Well Constructor H. W. Bartels  
Signature

Draw the diagram to show the full diameter and right section of well only.