

DEC 19 1975

NOTE

WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

1. COUNTY Crawford CHECK ONE  Town  Village  City NAME Eastman

2. LOCATION - 1/4 Section SW Section 3 Township 8N Range 5W 3. OWNER AT TIME OF DRILLING Leonard Check

OR - Grid or street no. Street name ADDRESS RFD

AND - If available subdivision name, lot & block no. POST OFFICE Steubens Wis., 54657

4. Distance in feet from well to nearest:

BUILDING	SANITARY SEWER	FLOOR DRAIN	FOUNDATION DRAIN	WASTE WATER DRAIN
C. I.	C. I.	C. I.	SEWER CONNECTED	C. I.
TILE	TILE	TILE	INDEPENDENT	TILE
<u>60'</u>	<u>125'</u>	<u>125'</u>		

CLEAR WATER DRAIN	SEPTIC TANK	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILLO	ABANDONED WELL	SINK HOLE
C. I.	TILE							
	<u>150'</u>			<u>180'</u>	<u>100'</u>		<u>50'</u>	

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Farm home

6. DRILLHOLE						9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
<u>10</u>	<u>Surface</u>	<u>244</u>	<u>6</u>	<u>244</u>	<u>420</u>	<u>Clay</u>	<u>Surface</u>	<u>10</u>
						<u>limestone</u>	<u>10</u>	<u>60</u>
						<u>soft sandstone</u>	<u>60</u>	<u>220</u>
						<u>limestone</u>	<u>220</u>	<u>390</u>
						<u>sandstone</u>	<u>390</u>	<u>420</u>

7. CASING, LINER, CURBING, AND SCREEN

Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
<u>6</u>	<u>new black steel plain end 18.97</u>	<u>Surface</u>	<u>244</u>
	<u>A-53</u>		
	<u>Valley Steel</u>		

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
<u>Cement</u>	<u>Surface</u>	<u>244</u>

10. TYPE OF DRILLING MACHINE USED

Cable Tool  Direct Rotary  Reverse Rotary

Rotary - air w/drilling mud  Rotary - hammer with drilling mud & air  Jetting with Air  Water

Well construction completed on 11-15-1975

11. MISCELLANEOUS DATA

Yield test: 3 Hrs. at 8 GPM

Well is terminated 14 inches  above  below final grade

Depth from surface to normal water level 340 ft. Well disinfected upon completion  Yes  No

Depth to water level when pumping 360 ft. Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on: 12-15-1975

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Kenneth Coplan Registered Well Driller COMPLETE MAIL ADDRESS Booscobel Wis., 53805

R3 Box 84

Please do not write in space below

COLIFORM TEST RESULT	GAS - 24 HRS.	GAS - 48 HRS.	CONFIRMED	REMARKS
<u>574</u>				

REV. 3-71