

WELL CONSTRUCTOR'S REPORT  
FORM 3300-15

FEB 16, 1973 ✓

STATE OF WISCONSIN  
DEPARTMENT OF NATURAL RESOURCES  
Box 450  
Madison, Wisconsin 53701

NOTE  
WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

15124

1. COUNTY Crawford CHECK ONE  Town  Village  City NAME Wauzeka

2. LOCATION - 1/4 Section SW Section 4 Township 8 N Range 5 W 3. OWNER AT TIME OF DRILLING Don Rose

OR - Grid or street no. Street name ADDRESS R7D Wauzeka, Wis.

AND - If available subdivision name, lot & block no. POST OFFICE 53826

4. Distance in feet from well to nearest: BUILDING 15' SANITARY SEWER C.I. 25' TILE FLOOR DRAIN C.I. TILE FOUNDATION DRAIN SEWER CONNECTED INDEPENDENT WASTE WATER DRAIN C.I. 25' TILE

CLEAR WATER DRAIN C.I. TILE SEPTIC TANK 60' PRIVY SEEPAGE PIT 80' ABSORPTION FIELD BARN SILO ABANDONED WELL SINK HOLE

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Country home

6. DRILLHOLE						9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
10	Surface	80	6	80	100	Clay	Surface	30
						loose stone & Clay	30	60
						hard shale stone	60	80
						sandstone	80	100

7. CASING, LINER, CURBING, AND SCREEN			
Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
6	new black steel plain end 19.18	Surface	80

8. GROUT OR OTHER SEALING MATERIAL			10. TYPE OF DRILLING MACHINE USED		
Kind	From (ft.)	To (ft.)	<input type="checkbox"/> Cable Tool	<input type="checkbox"/> Direct Rotary	<input type="checkbox"/> Reverse Rotary
Clay	Surface	30	<input type="checkbox"/> Rotary - air w/drilling mud	<input checked="" type="checkbox"/> Rotary - hammer with drilling mud & air	<input type="checkbox"/> Jetting with Air <input type="checkbox"/> Water
Cement	30	80	Well construction completed on 1-15-1973		

11. MISCELLANEOUS DATA  
Yield test: 3 Hrs. at 6 GPM  
Well is terminated 10 inches  above  below final grade  
Depth from surface to normal water level 65 ft. Well disinfected upon completion  Yes  No  
Depth to water level when pumping 65 ft. Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on: 2-12-1973

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Herbert Coplan Registered Well Driller COMPLETE MAIL ADDRESS R3 Box 84 Boscobel, Wis. 53805

COLIFORM TEST RESULT 577 GAS - 24 HRS. GAS - 48 HRS. CONFIRMED REMARKS  
REV. 3-71