

INSTRUCTIONS

ALL INFORMATION INDICATED ON THE FACE OF THIS FORM MUST BE GIVEN

PLEASE BE GUIDED BY THE FOLLOWING:

Numbers below correspond to numbers of items of the form on the opposite side.

1. Name of the County and the name of the Town, Village or City. Indicate which is given.
2. If Rural: Number and the $\frac{1}{4}$ of the Section, the number of the Town North, and the number of the Range East or West.
If Urban: Name of the Street and the number of the Premise.
3. Name of the Owner. If the name of the owner cannot be given, give instead the name of the Agent. Indicate which is given.
4. Name of the Street and the number of the Premise or the number of the Mail Route, the name of the Post Office and the name of the State.
5. Distance, in feet, from the well to the nearest building and to each source of pollution shown.
6. Indicate: Home, farm, school, tavern, creamery, community, industry, etc.
7. Show the diameter and depth of the initial drillhole or excavation and each reduction in size to bottom. If well was reconstructed, show diameter and depth of original well on first line.
8. Show diameter and kind of casing pipe, liner pipe or curbing and actual position in the well, measured from the surface.
9. Show kind of material (mud or cement) used in sealing the annular space, from and to what depths from the surface. If neither was used indicate "none".
10. Show thickness of each formation and the total depth at the base thereof.
11. Provide the data indicated.

Note: The Well Construction Report (Well Log) may be forwarded with the water sample from a newly constructed or reconstructed well, instead of the report requested by the State Laboratory of Hygiene, on the form which accompanies the sample bottle.

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, subsurface pumphrooms, access pits, etc., may be given here:

Casing with drive shoe driven from 15 ft to 81 ft.
Driven into good firm foundation but could
be driven further. Clay slurry used for
grout from 0 to 15 ft. instead of cement. As casing
could be driven further later if needed.

If more space is needed another sheet may be attached.