

JAN 29 1974

WELL CONSTRUCTOR'S REPORT  
FORM 3300-15

STATE OF WISCONSIN  
DEPARTMENT OF NATURAL RESOURCES  
Box 450  
Madison, Wisconsin 53701

NOTE  
WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

1. COUNTY Crawford CHECK ONE  Town  Village  City NAME Eastman

2. LOCATION - 1/4 Section SE Section 31 Township 8N Range 7W 3. OWNER AT TIME OF DRILLING Roy Zimmerman

OR - Grid or street no. Street name (6) ADDRESS R7D

AND - If available subdivision name, lot & block no. POST OFFICE Kauzeka, Wis. 53826

4. Distance in feet from well to nearest:

|                |                     |                   |                                  |                              |                         |                        |
|----------------|---------------------|-------------------|----------------------------------|------------------------------|-------------------------|------------------------|
| BUILDING C. I. | SANITARY SEWER TILE | FLOOR DRAIN C. I. | FOUNDATION DRAIN SEWER CONNECTED | FOUNDATION DRAIN INDEPENDENT | WASTE WATER DRAIN C. I. | WASTE WATER DRAIN TILE |
| <u>10'</u>     | <u>15'</u>          |                   |                                  |                              |                         |                        |

(Record answer in appropriate block)

|                         |                  |       |             |                  |      |       |                |           |
|-------------------------|------------------|-------|-------------|------------------|------|-------|----------------|-----------|
| CLEAR WATER DRAIN C. I. | SEPTIC TANK TILE | PRIVY | SEEPAGE PIT | ABSORPTION FIELD | BARN | SILLO | ABANDONED WELL | SINK HOLE |
|                         | <u>60'</u>       |       |             | <u>80'</u>       |      |       |                |           |

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Country home

| 6. DRILLHOLE |                |            |            |            |            | 9. FORMATIONS           |                |            |  |
|--------------|----------------|------------|------------|------------|------------|-------------------------|----------------|------------|--|
| Dia. (in.)   | From (ft.)     | To (ft.)   | Dia. (in.) | From (ft.) | To (ft.)   | Kind                    | From (ft.)     | To (ft.)   |  |
| <u>10</u>    | <u>Surface</u> | <u>285</u> | <u>6</u>   | <u>285</u> | <u>500</u> | <u>Clay</u>             | <u>Surface</u> | <u>20</u>  |  |
|              |                |            |            |            |            | <u>limestone</u>        | <u>20</u>      | <u>120</u> |  |
|              |                |            |            |            |            | <u>soft sandstone</u>   | <u>120</u>     | <u>210</u> |  |
|              |                |            |            |            |            | <u>Clay &amp; stone</u> | <u>210</u>     | <u>260</u> |  |
|              |                |            |            |            |            | <u>limestone</u>        | <u>260</u>     | <u>460</u> |  |
|              |                |            |            |            |            | <u>sandstone</u>        | <u>460</u>     | <u>500</u> |  |

7. CASING, LINER, CURBING, AND SCREEN

| Dia. (in.) | Kind and Weight                        | From (ft.)     | To (ft.)   |
|------------|--|----------------|------------|
| <u>6</u>   | <u>new black steel plain end 19.18</u> | <u>Surface</u> | <u>285</u> |

8. GROUT OR OTHER SEALING MATERIAL

| Kind          | From (ft.)     | To (ft.)   |
|---------------|----------------|------------|
| <u>Clay</u>   | <u>Surface</u> | <u>20</u>  |
| <u>Cement</u> | <u>20</u>      | <u>285</u> |

10. TYPE OF DRILLING MACHINE USED

Cable Tool  Direct Rotary  Reverse Rotary

Rotary - air w/drilling mud  Rotary - hammer with drilling mud & air  Jetting with  Air  Water

Well construction completed on 1 - 7 - 1974

11. MISCELLANEOUS DATA

Yield test: 4 Hrs. at 9 GPM

Depth from surface to normal water level 410 ft.

Depth to water level when pumping 430 ft.

Well is terminated 12 inches  above  below final grade

Well disinfected upon completion  Yes  No

Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on: 1 - 21 - 1974

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Henneth Coplan Registered Well Driller COMPLETE MAIL ADDRESS R3 Box 84 Boesobel, Wis. 53805

Please do not write in space below

|                                 |               |               |           |         |
|---------------------------------|---------------|---------------|-----------|---------|
| COLIFORM TEST RESULT <u>656</u> | GAS - 24 HRS. | GAS - 48 HRS. | CONFIRMED | REMARKS |
|---------------------------------|---------------|---------------|-----------|---------|