

WELL CONSTRUCTOR'S REPORT  
FORM 3300-15

JUN 18 1975

NOTE  
WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

STATE OF WISCONSIN  
DEPARTMENT OF NATURAL RESOURCES  
Box 450  
Madison, Wisconsin 53701

1. COUNTY Crawford CHECK ONE  Town  Village  City NAME Scott

2. LOCATION - 1/4 Section NE Section 4 Township 9N Range 3W 3. OWNER AT TIME OF DRILLING Mr. Kenneth Fiedler  
OR - Grid or street no. Street name ADDRESS R 7 D

AND - If available subdivision name, lot & block no. POST OFFICE Gay Mills, Wis. 54631

4. Distance in feet from well to nearest:  
(Record answer in appropriate block)

BUILDING C. I.	SANITARY SEWER TILE	FLOOR DRAIN C. I.	TILE	FOUNDATION DRAIN SEWER CONNECTED	INDEPENDENT	WASTE WATER DRAIN C. I.	TILE		
	<u>75'</u>	<u>140'</u>							
CLEAR WATER DRAIN C. I.	TILE	SEPTIC TANK	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILO	ABANDONED WELL	SINK HOLE
		<u>160'</u>		<u>170'</u>		<u>75'</u>			

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Country home

6. DRILLHOLE

Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	9. FORMATIONS Kind	From (ft.)	To (ft.)
<u>10</u>	<u>Surface</u>	<u>40</u>	<u>6</u>	<u>40</u>	<u>100</u>	<u>Clay</u>	<u>Surface</u>	<u>30</u>
						<u>limestone</u>	<u>30</u>	<u>75</u>
						<u>sandstone</u>	<u>75</u>	<u>100</u>

7. CASING, LINER, CURBING, AND SCREEN

Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
<u>6</u>	<u>new black steel plain end 18.97</u>	<u>Surface</u>	<u>40</u>

8. GROUT OR OTHER SEALING MATERIAL

Kind	From (ft.)	To (ft.)
<u>Clay</u>	<u>Surface</u>	<u>30</u>
<u>Cement</u>	<u>30</u>	<u>40</u>

10. TYPE OF DRILLING MACHINE USED  
 Cable Tool  Direct Rotary  Reverse Rotary  
 Rotary - air w/drilling mud  Rotary - hammer with drilling mud & air  Jetting with Air  Water

Well construction completed on 5-22-1975

11. MISCELLANEOUS DATA

Yield test: 3 Hrs. at 8 GPM

Well is terminated 12 inches  above  below final grade

Depth from surface to normal water level 60 ft. Well disinfected upon completion  Yes  No

Depth to water level when pumping 68 ft. Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on: 6-9-1975

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Kenneth Copian Registered Well Driller COMPLETE MAIL ADDRESS Boscobel, R3 Box 84 Wis., 53805

COLIFORM TEST RESULT 677 GAS - 24 HRS. GAS - 48 HRS. CONFIRMED REMARKS

REV. 3-71