

1. COUNTY Crawford CHECK ONE  Town  Village  City NAME Scott

2. LOCATION (Number and Street or 1/4 section, section, township and range. Also give subdivision name, lot and block numbers when available.)  
NW of SE of Sec. 16 T9N R3W

3. OWNER AT TIME OF DRILLING Lyle Meade

4. OWNER'S COMPLETE MAIL ADDRESS RD 8 Boscobel, Wis. 53805

5. Distance in feet from well to nearest: (Record answer in appropriate block)

|                |               |             |                  |                                  |                              |                         |                        |
|----------------|---------------|-------------|------------------|----------------------------------|------------------------------|-------------------------|------------------------|
| BUILDING C. I. | SANITARY TILE | SEWER C. I. | FLOOR DRAIN TILE | FOUNDATION DRAIN SEWER CONNECTED | FOUNDATION DRAIN INDEPENDENT | WASTE WATER DRAIN C. I. | WASTE WATER DRAIN TILE |
| 65'            |               | 70'         |                  |                                  |                              | 60'                     |                        |

|                         |                        |             |       |             |                  |      |      |                |           |
|-------------------------|------------------------|-------------|-------|-------------|------------------|------|------|----------------|-----------|
| CLEAR WATER DRAIN C. I. | CLEAR WATER DRAIN TILE | SEPTIC TANK | PRIVY | SEEPAGE PIT | ABSORPTION FIELD | BARN | SILO | ABANDONED WELL | SINK HOLE |
|                         |                        | 70'         |       | 80'         |                  | 125' | 115' | 40'            |           |

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

6. Well is intended to supply water for: Farm home

| 7. DRILLHOLE |            |          |            |            |          | 10. FORMATIONS |            |          |
|--------------|------------|----------|------------|------------|----------|----------------|------------|----------|
| Dia. (in.)   | From (ft.) | To (ft.) | Dia. (in.) | From (ft.) | To (ft.) | Kind           | From (ft.) | To (ft.) |
| 10           | Surface    | 60       | 6          | 60         | 395      | Clay           | Surface    | 20       |
|              |            |          |            |            |          | limestone      | 20         | 200      |

| 8. CASING, LINER, CURBING, AND SCREEN |                           |            |          |           |
|---------------------------------------|---------------------------|------------|----------|-----------|
| Dia. (in.)                            | Kind and Weight           | From (ft.) | To (ft.) |           |
| 6                                     | new black plain end 19.18 | Surface    | 60       | sandstone |
|                                       |                           |            |          | limestone |
|                                       |                           |            |          | sandstone |

| 9. GROUT OR OTHER SEALING MATERIAL |            |          |
|------------------------------------|------------|----------|
| Kind                               | From (ft.) | To (ft.) |
| Clay                               | Surface    | 20       |
| Cement                             | 20         | 60       |

11. MISCELLANEOUS DATA  
 Yield test: 12 Hrs. at 15 GPM Well is terminated 20 inches  above  below final grade

Depth from surface to normal water level 310 ft. Well disinfected upon completion  Yes  No

Depth to water level when pumping 315 ft. Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on: 9-25- 1967

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Benneth Coplan Registered Well Driller COMPLETE MAIL ADDRESS R3 Box 84 Boscobel, Wis. 53805

Please do not write in space below

|                      |               |               |           |         |
|----------------------|---------------|---------------|-----------|---------|
| COLIFORM TEST RESULT | GAS - 24 HRS. | GAS - 48 HRS. | CONFIRMED | REMARKS |
| 698                  |               |               |           |         |