

WELL CONSTRUCTOR'S REPORT  
FORM 3300-15

NOV 26 1971  
NOTE

STATE OF WISCONSIN  
DEPARTMENT OF NATURAL RESOURCES  
Box 450  
Madison, Wisconsin 53701

WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

1. COUNTY Crawford CHECK ONE  Town  Village  City NAME Scott

2. LOCATION - 1/4 Section SW Section 33 Township 9N Range 3W 3. OWNER AT TIME OF DRILLING Keith Yahn Jr.

OR - Grid or street no. Street name ADDRESS R7B

AND - If available subdivision name, lot & block no. POST OFFICE Boscobel, Wis., 53805

4. Distance in feet from well to nearest:

BUILDING	SANITARY SEWER	FLOOR DRAIN	FOUNDATION DRAIN	WASTE WATER DRAIN
C.I.	C.I.	C.I.	SEWER CONNECTED	C.I.
TILE	TILE	TILE	INDEPENDENT	TILE
<u>8'</u>	<u>30'</u>	<u>35'</u>		<u>35'</u>

(Record answer in appropriate block)

CLEAR WATER DRAIN	SEPTIC TANK	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILLO	ABANDONED WELL	SINK HOLE
C.I.	TILE							
	<u>50'</u>			<u>65'</u>				

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Country home

6. DRILLHOLE						9. FORMATIONS			
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)	
<u>10</u>	<u>Surface</u>	<u>60</u>	<u>6</u>	<u>60</u>	<u>100</u>	<u>Clay</u>	<u>Surface</u>	<u>20</u>	
						<u>Clay &amp; broken stone</u>	<u>20</u>	<u>40</u>	
						<u>hard shale stone</u>	<u>40</u>	<u>80</u>	
						<u>sandstone</u>	<u>80</u>	<u>100</u>	

8. GROUT OR OTHER SEALING MATERIAL				10. TYPE OF DRILLING MACHINE USED			
Kind	From (ft.)	To (ft.)					
<u>Clay</u>	<u>Surface</u>	<u>20</u>	<input type="checkbox"/> Cable Tool	<input type="checkbox"/> Direct Rotary	<input type="checkbox"/> Reverse Rotary	<input type="checkbox"/> Jetting with	
<u>Cement</u>	<u>20</u>	<u>60</u>	<input type="checkbox"/> Rotary - air w/drilling mud	<input checked="" type="checkbox"/> Rotary - hammer with drilling mud & air	<input type="checkbox"/> Air	<input type="checkbox"/> Water	

Well construction completed on 11-18-1971

11. MISCELLANEOUS DATA

Yield test: 2 Hrs. at 12 GPM

Well is terminated 10 inches  above  below final grade

Depth from surface to normal water level 40 ft. Well disinfected upon completion  Yes  No

Depth to water level when pumping 64 ft. Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on: 11-22-1971

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Kenneth Copman Registered Well Driller COMPLETE MAIL ADDRESS Boscobel, R3 Box 84, Wis., 53805

Please do not write in space below

COLIFORM TEST RESULT <u>727</u>	GAS - 24 HRS.	GAS - 48 HRS.	CONFIRMED	REMARKS
REV. 3-71				