

WELL CONSTRUCTOR'S REPORT  
FORM 3300-15

AUG 31 1973

NOTE 34167

WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

STATE OF WISCONSIN  
DEPARTMENT OF NATURAL RESOURCES  
Box 450  
Madison, Wisconsin 53701

1. COUNTY Crawford CHECK ONE  Town  Village  City NAME Haney

2. LOCATION - 1/4 Section SW Section 3 Township 9N Range 4W 3. OWNER AT TIME OF DRILLING Byron Ambrose

OR - Grid or street no. Street name ADDRESS R 7th

AND - If available subdivision name, lot & block no. POST OFFICE Says Mills, Wis. 54631

4. Distance in feet from well to nearest: BUILDING 25' SANITARY SEWER C.I. 40' FLOOR DRAIN C.I. 40' FOUNDATION DRAIN SEWER CONNECTED INDEPENDENT WASTE WATER DRAIN C.I. TILE

(Record answer in appropriate block)

CLEAR WATER DRAIN C.I. TILE SEPTIC TANK 80' PRIVY SEEPAGE PIT 90' ABSORPTION FIELD BARN SILO ABANDONED WELL SINK HOLE

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Country home

6. DRILLHOLE						9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
6	Surface	100				loose sand	Surface	60
						sandstone	60	100

8. GROUT OR OTHER SEALING MATERIAL				10. TYPE OF DRILLING MACHINE USED			
Kind	From (ft.)	To (ft.)					
loose sand	Surface	60	<input type="checkbox"/> Cable Tool	<input type="checkbox"/> Direct Rotary	<input type="checkbox"/> Reverse Rotary	<input type="checkbox"/> Jetting with Air	<input type="checkbox"/> Jetting with Water
			<input type="checkbox"/> Rotary - air w/drilling mud	<input checked="" type="checkbox"/> Rotary - hammer with drilling mud & air			

11. MISCELLANEOUS DATA

Yield test: 3 Hrs. at 8 GPM

Well is terminated 10 inches  above  below final grade

Depth from surface to normal water level 60 ft. Well disinfected upon completion  Yes  No

Depth to water level when pumping 60 ft. Well sealed watertight upon completion  Yes  No

Water sample sent to Madison laboratory on: 8-28- 19 73

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side.

SIGNATURE Kenneth Copian Registered Well Driller COMPLETE MAIL ADDRESS R3 Box 84 Boscobel, Wis., 53805

Please do not write in space below

COLIFORM TEST RESULT	GAS - 24 HRS.	GAS - 48 HRS.	CONFIRMED	REMARKS
736				