WELL LOG and REPORT

For method of making report, refer to	bulletin entitled "Well Constru	uction R	eport," 7-5-39. Accuracy is essential.	· · · · · · · · · · · · · · · · · · ·
In this column indicate the kind of casing, liner, shoe and other accessories used.	WELL DIAGRAM Use a red line to show or liner pipe. Use black fo or borehole.	casing or drill	In this column state the kind of formations penetrated, their thickness in feet and if water bearing.	Record of FINAL Pumping test
HI feet of 5" Standard Steel Black (iron) Casing.	Inches Diameter 2 3 4 5 6 8 10121416	Depth	HEavy Brack	Duration of test Hours 6 Rra
Casing.		25	ChA4.	Pumping rate G.P.M. 79. M Depth of pump in 70 75 well. Ft. 70 75
			RUCK.	Depth of pump in 70 75 well. Ft. 70
		50	•	Standing water-level (from surface) Ft. 55
		75		Water-level when pumping Ft. Same.
DEPTHOF PELL		-1 00 -		Water. End of test. Clear Clear Cloudy Turbid
	, ,	150		Was the well sterilized? YesNo
		200		To which laboratory was sample sent? Madison Date Oct 6, /94/
		400		Was the well sealed on completion? Yes Yes No.
				How high did you leave the casing-pipe above grade?
		800		Well was completed Date Qt / 9.4
·	Draw the diagram to show full diameter and right sect	1200		Well Constructor A. W. Bartel
765-R	well only.	-V V4	}	Signature