

AUG 11 1972

WELL CONSTRUCTOR'S REPORT  
FORM 3300-15

STATE OF WISCONSIN  
DEPARTMENT OF NATURAL RESOURCES  
Box 450  
Madison, Wisconsin 53701

NOTE  
WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

1. COUNTY **Crawford** CHECK ONE  Town  Village  City NAME **Seneca**

2. LOCATION - 1/4 Section Section Township Range  
**SW 1/4 | NW 1/4 | 25 | 9-n | 5-W**

3. OWNER AT TIME OF DRILLING **Rinehart Mischel**  
OR - Grid or street no. Street name ADDRESS **R.R.**

AND - If available subdivision name, lot & block no. POST OFFICE **Seneca, Wisc.**

4. Distance in feet from well to nearest: (Record answer in appropriate block)

BUILDING	SANITARY SEWER C.I.	FILE	FLOOR DRAIN C.I.	FILE	FOUNDATION DRAIN SEWER CONNECTED	INDEPENDENT	WASTE WATER DRAIN C.I.	FILE
35	35		110		None		None	

CLEAR WATER DRAIN C.I.	TILE	SEPTIC TANK	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILO	ABANDONED WELL	SINK HOLE
None		80	None	180	None	120	100	None	None

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)  
**None**

5. Well is intended to supply water for: **Grade B Dairy Farm & Residence**

6. DRILLHOLE						9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
10	Surface	68	6	68	277	Soft Brn. Limestone	Surface	55
						Hard Brn. Limestone	55	68

7. CASING, LINER, CURBING, AND SCREEN			
Dia. (in.)	Kind and Weight	From (ft.)	To (ft.)
6	New Steel P.E.	Surface	68
	18.97# per ft.		

Recasing Job  
No other samples available

8. GROUT OR OTHER SEALING MATERIAL			10. TYPE OF DRILLING MACHINE USED		
Kind	From (ft.)	To (ft.)	<input checked="" type="checkbox"/> Cable Tool	<input type="checkbox"/> Direct Rotary	<input type="checkbox"/> Reverse Rotary
Neat Cement	Surface	68	<input type="checkbox"/> Rotary - air w/drilling mud	<input type="checkbox"/> Rotary - hammer with drilling mud & air	<input type="checkbox"/> Jetting with <input type="checkbox"/> Air <input type="checkbox"/> Water
			Well construction completed on <b>8-8 1972</b>		

11. MISCELLANEOUS DATA			
Yield test:	5	Hrs. at	14 GPM
Depth from surface to normal water level	215	ft.	
Depth to water level when pumping	245	ft.	

Well is terminated **18** inches  above  below final grade

Well disinfected upon completion  Yes  No

Well sealed watertight upon completion  Yes  No

Water sample sent to **State lab. of Hygiene; Madison, Wisc.** laboratory on: **8-9 1972**

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumprooms, access pits, etc., should be given on reverse side. See Reverse Side

SIGNATURE *Duane Lubbers* COMPLETE MAIL ADDRESS **Duane Lubbers**  
**Duane Lubbers** **W.D. 410** **Registered Well Driller** **Farmersburg, Iowa 52047**

Please do not write in space below

COLIFORM TEST RESULT <b>783</b>	GAS - 24 HRS.	GAS - 48 HRS.	CONFIRMED	REMARKS
------------------------------------	---------------	---------------	-----------	---------

WGNHS ORIGINAL