

WELL LOG and REPORT

In this column indicate the kind of casing, liner, shoe and other accessories used.	WELL DIAGRAM Use a red line to show casing or liner pipe. Use black for drill or borehole.	In this column state the kind of formations penetrated, their thickness in feet and if water bearing.	Record of FINAL Pumping test	
5" Steel Well Casing Drive Shoe Sanitary Pump Flange	Inches Diameter 2 3 4 5 6 8 10 12 14 16 18	Depth		
		12	Top Soil 12'	Duration of test Hours <u>2</u>
		25	Limerock 58'	Pumping rate G.P.M. <u>10</u>
		50		Depth of pump in well. Ft. <u>115</u>
		70		Standing water-level (from surface) Ft. <u>75</u>
		75		Water-level when pumping Ft. <u>70</u>
		100	Water Bearing Shale 45'	Water. End of test. Clear <input checked="" type="checkbox"/> Cloudy _____ Turbid _____
		115		Was the well sterilized? Yes <input checked="" type="checkbox"/> No _____
		150		To which laboratory was sample sent? <u>Madison, Wis</u> Date <u>April 24, 1939</u>
		200		Was the well sealed on completion? Yes _____ No <input checked="" type="checkbox"/>
	400		How high did you leave the casing-pipe above grade? <u>8"</u>	
	800		Well was completed Date <u>April 22, 1939</u>	
	1200		Well Driller <u>Kochandorfer & Sons</u> Signature	

Draw the diagram to show the right half only