

WELL CONSTRUCTOR'S REPORT  
FORM 3300-15

JUN 19 1974

JUL 1 - 1974

STATE OF WISCONSIN  
DEPARTMENT OF NATURAL RESOURCES  
Box 450  
Madison, Wisconsin 53701

NOTE

WHITE COPY - DIVISION'S COPY  
GREEN COPY - DRILLER'S COPY  
YELLOW COPY - OWNER'S COPY

1. COUNTY Crawford CHECK ONE  Town  Village  City Clayton

2. LOCATION - 1/4 Section NW Section 3 Township 10N Range 3W

OR - Grid or street no. \_\_\_\_\_ Street name \_\_\_\_\_

3. OWNER AT TIME OF DRILLING Donald M. Johnson  
ADDRESS R2 Box 155  
POST OFFICE Soldiers Grove, Wis. 54655

4. Distance in feet from well to nearest:  
(Record answer in appropriate block)

BUILDING C. I.	SANITARY SEWER TILE	FLOOR DRAIN C. I.	FOUNDATION DRAIN SEWER CONNECTED	FOUNDATION DRAIN INDEPENDENT	WASTE WATER DRAIN C. I.	WASTE WATER DRAIN TILE		
<u>12'</u>	<u>18'</u>	<u>18'</u>						
CLEAR WATER DRAIN C. I.	SEPTIC TANK TILE	PRIVY	SEEPAGE PIT	ABSORPTION FIELD	BARN	SILLO	ABANDONED WELL	SINK HOLE
	<u>75'</u>			<u>85'</u>	<u>125'</u>			

OTHER POLLUTION SOURCES (Give description such as dump, quarry, drainage well, stream, pond, lake, etc.)

5. Well is intended to supply water for: Farm home

6. DRILLHOLE						9. FORMATIONS		
Dia. (in.)	From (ft.)	To (ft.)	Dia. (in.)	From (ft.)	To (ft.)	Kind	From (ft.)	To (ft.)
<u>10</u>	<u>Surface</u>	<u>246</u>	<u>6</u>	<u>246</u>	<u>320</u>	<u>Clay</u>	<u>Surface</u>	<u>15</u>
						<u>sandstone</u>	<u>15</u>	<u>35</u>
						<u>limestone</u>	<u>35</u>	<u>200</u>
						<u>soft sandstone</u>	<u>200</u>	<u>230</u>
						<u>hard sandstone</u>	<u>230</u>	<u>320</u>

8. GROUT OR OTHER SEALING MATERIAL			10. TYPE OF DRILLING MACHINE USED		
Kind	From (ft.)	To (ft.)	<input type="checkbox"/> Cable Tool	<input type="checkbox"/> Direct Rotary	<input type="checkbox"/> Reverse Rotary
<u>Clay</u>	<u>Surface</u>	<u>15</u>	<input type="checkbox"/> Rotary - air w/drilling mud	<input checked="" type="checkbox"/> Rotary - hammer with drilling mud & air	<input type="checkbox"/> Jetting with <input type="checkbox"/> Air <input type="checkbox"/> Water
<u>Cement</u>	<u>15</u>	<u>246</u>	Well construction completed on <u>5-29-1974</u>		

11. MISCELLANEOUS DATA		
Yield test:	<u>3</u> Hrs. at	<u>8</u> GPM
Depth from surface to normal water level	<u>270</u> ft.	
Depth to water level when pumping	<u>278</u> ft.	
Well is terminated	<u>10</u> inches	<input checked="" type="checkbox"/> above <input type="checkbox"/> below final grade
Well disinfected upon completion	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Well sealed watertight upon completion	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Water sample sent to Madison laboratory on: 6-13-1974

Your opinion concerning other pollution hazards, information concerning difficulties encountered, and data relating to nearby wells, screens, seals, type of casing joints, method of finishing the well, amount of cement used in grouting, blasting, sub-surface pumphrooms, access pits, etc., should be given on reverse side.

SIGNATURE Kenneth Coyian Registered Well Driller COMPLETE MAIL ADDRESS Boscobel, Wis., 53805  
R3 Box 84

COLIFORM TEST RESULT 849 GAS - 24 HRS. GAS - 48 HRS. CONFIRMED REMARKS

REV. 3-71